



39th Gas-Lift Workshop
Houston, Texas, USA
May 16 – 20, 2016

Batch Foaming Gas-lifted Oil and Liquid Loaded Gas wells in BSP

Olumuyiwa Owoyemi, PT & Gas-Lift aSME and

James W. Hall, Principal PT, Global PTE Artificial Lift
Brunei Shell Petroleum



Agenda

- **Introduction**
- **Candidate Selection**
- **Foamer Agent Selection**
- **Results**
- **Conclusion and Way forward**

Introduction

- East asset in BSP has several hundred producing wells. Mainly gas-lifted oil and gas wells
- Some oil wells have high water cut ($> 70\%$ BS&W). Here there is an opportunity to use batch foaming to provide short term production improvement and reduce Gas-lift (GL) consumption
- Some high rate gas wells have also gradually become liquid loaded and suffer kick off issues. Potential to use foamers to accelerate well kick off and reduce deferment

Candidate Selection

- **5 wells were selected for the foam trials (3 gas-lifted oil wells & 2 gas wells)**

Well	A	B	C	D	E
Fluid	Oil	Oil	Oil	Gas	Gas
Type	Flowing (Gas-lifted)	Flowing (Gas-lifted)	Flowing (Gas-lifted)	Dead	Huff and Puff

- **A, B & C –Partially loaded – Producing water**
- **D – Well with suspected inflow issue**
- **E – Flowing well with transient loading behaviour**

Foamer Agent Selection


Water samples from Well A and B were tested with 3 foamers supplied by Champion Nalco

- V-505 (water-foaming foamer)
- IVDF-140 (water-foaming foamer)
- IVDF-130 (water-foaming foamer)


Foamer IVDF-140 and IVDF-130 performed better than V-505. **IVDF140 Selected**

Foam Build up		Foam half Life	
Foam Build-up time (s)	Result	(s)	Result
< 80 s	Good	> 180 s	Good
80 < x < 120 s	Moderate	60 < x < 180 s	Moderate
> 120 s	Poor	> 60 s	Poor

Well A





Well B



DEPLOYMENT & APPLICATION METHOD

- The liquid foamer was batched into tubing via 1/2" NPT connection at the top of the wellhead shown below.

Anti-foam chemical was injected after flow back to minimize oil carry-over into gas line and avoid complication with level control in a separator or tank.



Foam Application Procedure


- An average of 120 liters of foamer (IVDF-140), followed by an average of 170 litres of overflush (KCL) was pumped into each well candidate.
- This was followed by a shut-in period of 18-24 hrs. Wells were flowed back to the test separator or main oil line (if a test separator was not available)

Results Overview


Overall the trial was successful with :

- **Well A (oil well)**
 - Initial flow back : Transient slugs
 - ~ 40% increase in gross (after two well tests 5 days apart) . Some reduction in initial Gas-lift consumption . The was maintained for around 5 months
- **Well B (Oil Well)**
 - Initial flow back showed ~10% increase in gross rate maintained for around 3 months
- **Well C (Oil Well)**
 - Initial flow back showed no change in measured gross
- **Well D (Gas well)**
 - 2 attempts at kicking off well . Well failed to respond
 - It was concluded that remediation must be performed to return well back to production
- **Well E (Gas well)**
 - 3 attempts at kicking off well . Well kicked off strongly after 3rd foam injection attempt. ~ 200ksm³/d gas production restored . Well is a gas-lift supplier supporting ~1000m³/d production

Results Detail – Well A- Gas-lifted Oil Well



Results Well E – High Gas Rate Well (Kick off)



Lessons Leant & Conclusion

Lessons Learnt

- Aggressive well start-up for initial foam unloading
- Alignment of Injection period and flow back periods with availability of onshore support
- If a wells fails to respond, try successive treatments of batch foam chemical before discontinuing trial

Conclusions and Way forward

- Batch foam injection is a viable low cost method of providing short term production improvement by reducing fluid level in the wellbore under flowing conditions.
- Batch foaming may also provide an alternative “poor boy” stimulation method for oil and gas wells
- Current efforts within BSP to mature continuous foam injection via Gas-lift

Copyright

Rights to this presentation are owned by the company(ies) and/or author(s) listed on the title page. By submitting this presentation to the Gas-Lift Workshop, they grant to the Workshop, the Artificial Lift Research and Development Council (ALRDC), and the American Society of Mechanical Engineers (ASME), rights to:

- Display the presentation at the Workshop.**
- Place it on the www.alrdc.com web site, with access to the site to be as directed by the Workshop Steering Committee.**
- Place it on a CD for distribution and/or sale as directed by the Workshop Steering Committee.**

Other uses of this presentation are prohibited without the expressed written permission of the company(ies) and/or author(s) who own it and the Workshop Steering Committee.

Disclaimer

The following disclaimer shall be included as the last page of a Technical Presentation or Continuing Education Course. A similar disclaimer is included on the front page of the Gas-Lift Workshop Web Site.

The Artificial Lift Research and Development Council and its officers and trustees, and the Gas-Lift Workshop Steering Committee members, and their supporting organizations and companies (here-in-after referred to as the Sponsoring Organizations), and the author(s) of this Technical Presentation or Continuing Education Training Course and their company(ies), provide this presentation and/or training material at the Gas-Lift Workshop "as is" without any warranty of any kind, express or implied, as to the accuracy of the information or the products or services referred to by any presenter (in so far as such warranties may be excluded under any relevant law) and these members and their companies will not be liable for unlawful actions and any losses or damage that may result from use of any presentation as a consequence of any inaccuracies in, or any omission from, the information which therein may be contained.

The views, opinions, and conclusions expressed in these presentations and/or training materials are those of the author and not necessarily those of the Sponsoring Organizations. The author is solely responsible for the content of the materials.

The Sponsoring Organizations cannot and do not warrant the accuracy of these documents beyond the source documents, although we do make every attempt to work from authoritative sources. The Sponsoring Organizations provide these presentations and/or training materials as a service. The Sponsoring Organizations make no representations or warranties, express or implied, with respect to the presentations and/or training materials, or any part thereof, including any warranties of title, non-infringement of copyright or patent rights of others, merchantability, or fitness or suitability for any purpose.